

## Specification

<b>Camera</b>	
Image Sensor	1/3" progressive scan CMOS
Min. Illumination	Color: 0.01 lux @ (F1.2, AGCON), 0 Lux with IR
Shutter Speed	1/3s to 1/100,000s, support slow shutter
Lens	2.8 mm @ F2.0, horizontal field of view 105.0°, 4 mm @ F2.0, horizontal field of view 83.0° 6 mm @ F2.0, horizontal field of view 55°
Lens Mount	M12
Day & Night	IR cut filter with auto switch
3-Axis Adjustment (Buckle)	Pan: 0° to 360°, Tilt: -90° to 90°, rotation: 0° to 360°
DNR(Digital Noise Reduction)	3D DNR
WDR (Wide Dynamic Range)	Digital WDR
<b>Compression Standard</b>	
Video Compression	Main stream H.264+H.265 Sub streams H.264/MJPEG
H.264 Type	Main Profile/Hig h profile
Video Bit Rate	32 Kbps to 16 Mbps
<b>Image</b>	
Max. Resolution	2688 × 1520
Main Stream	SDI: 20fps @ (2688 × 1520), 20fps @ (2304 × 1296), 20fps @ (1920 × 1080), 1280 × 720) 60fps: 20fps @ (2688 × 1520), 20fps @ (2304 × 1296), 30fps @ (1920 × 1080), 1280 × 720)
Sub Stream	SDI: 25fps @ (640 × 360), 30.24 × 2048) 60fps: 30fps @ (640 × 360), 35.2 × 240)
Image Settings	Brightness, saturation, contrast, sharpness are adjustable via web browser or client software
Day/Night Switch	Support auto, scheduled
Others	Mirror, HLC (area configurable), region of interest (support 1 fixed region)
<b>Network</b>	
Network Storage	NAS (PFSense)
Detections	Motion detection
Alarms	Video tampering, network disconnected, IP address conflicted
Protocols	TCP/IP/ICMP/HTTP/HTTSP, FTP/DHCP,DNS,DDNS,RTSP,RTSP/RTCP, NTP,UPnP,MS-SAMP,IGMPv3,LLMNR,DNS,Bonjour
Standard	ONVIF/PROFILE S, PROFILE G,PSIA,CGI,SAPI
General Function	Anti-flicker, heat filter, mirror, password protection, privacy mask, watermark, IP address filter
<b>Interface</b>	
Communication Interface	1 RJ-45 LOM/100M self-adaptive Ethernet port
<b>General</b>	
Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F), humidity: 95% or less (non-condensing)
Power Supply	12 VDC ± 25%, PoE (802.3af)
Power Consumption	Max. 5 W/6.5 W (PoE)
Ingress Protection	IP67
IR Range	Up to 30 m
Dimensions	69.1 mm×66 mm×172.7 mm (2.7"×2.6"×6.8")
Weight	500g (1.1 lb.)